

压电式载荷传感器

						
型 号	LC-YD-301	LC-YD-303	LC-YD-305	LC-YD-311A	LC-YD-312A	LC-YD-320
编 号	CG0028	CG0029	CG0030	CG0031	CG0032	CG0033
测 量 范 围	0~5KN	0~2KN	0~60KN	0~30KN	0~5KN	0~200KN
灵 敏 度	120pc/N	120pc/N	120pc/N	120pc/N	120pc/N	120pc/N
非 线 性	<1%	<1%	<1%	<1%	<1%	<1%
工 作 温 度	-40~+120℃	-40~+150℃	-40~+150℃	-40~+150℃	-40~+150℃	-40~+150℃
特 点	体积小 安装方便	响应快 小量程	刚度高 响应快	刚度高 响应快	刚度高 响应快	大量程 响应快

压电式载荷传感器

						
型号	LC-YD-360	LC-YD-3100	LC-YD-3302A	LC-YD-3310A	LC-YD-312A	LC-YD-320
编号	CG0034	CG0035	CG0036	CG0037	CG0038	CG0039
测量范围	0~600KN	0~1000KN	Z: ±20 KN X、Y: ±5KN	Z: ±100KN X、Y: ±30KN	F: 0~1KN A: 400gKN	F: 0~1KN A: 100gKN
灵敏度	2pc/N	2pc/N	Z: 3.5 pc/N X、Y: 7.5 pc/N	Z: 1.8pc/N X、Y: 3.6 pc/N	F: 4pc/N A: 50pC/g	F: 5mV/N A: 50mV/g
非线性	<1%	<1%	<1%	<1%	<1%	<1%
工作温度	-40~+150℃	-40~+150℃	-40~+150℃	-40~+150℃	-40~+150℃	-40~+150℃
特点	大量程 响应快	响应快 小量程	三向动态 力测量	大量程 三向力测量	力和加速度集合 一体	IEPE 力和加速度集 成一体