






型号	LC-YZ11	LC-YZ15	LC-YZ51
编号	CG0046	CG0047	CG0048
测量范围	-100kPa ~+100MPa	-100kPa ~+100MPa	-100kPa ~+100MPa
输出信号	4~20mA、0~5V DC	4~20mA	4~20mA、0~5V DC
供电电压	9~36V DC	9~36V DC	9~36V DC
精度等级	1%F.S、0.25%F.S	1%F.S、0.25%F.S	1%F.S、0.25%F.S
工作温度	-40~+85℃	-40~+85℃	-40~+85℃
应用	室内液体或气体的压强测量	气缸、管道压力测试	室内、粘性液体的压强测量

### 压电式压力传感器

						
型号	LC-YD-200	LC-YD-202	LC-YD-203	LC-YD-205	LC-YD-211	LC-YD-214
编号	CG0049	CG0050	CG0051	CG0052	CG0053	CG0054
测量范围	0~15MPa	0~10MPa	0~30MPa 0~60MPa	0~30MPa 0~60MPa	0~1MPa 0~5MPa	0~200MPa
灵敏度	20pc/0.1MPa	35pc/0.1MPa	12pc/0.1MPa	12pc/0.1MPa	5000~30000 pc/0.1MPa	3pc/0.1MPa
非线性	<1%	<1%	<1%	<1%	<5%	<1%
工作温度	-40~+300℃	-10~+80℃	-40~+150℃	-40~+150℃	-40~+80℃	-40~+150℃
应用	气缸、管道压力测试	冲击压力波测量	管道压力、爆炸压力测量	管道压力、爆炸压力测量	微小动态、压力测量、管道泄漏	爆炸压力测量